


Hyperion™

Orbit-A Delivery System

for ASDO and PFOO



Product Information

Features

- Pre-curved PTFE Sheath
- PTFE dilator
- Transparent loader
- Wide size ID / Small size OD
- Pusher cable with screw connection


Sizing

- 5 sizes
- Ø 8 to 14 F
- Pre-shaped angle: 135°
- Length sheath: 80 cm
- Length pusher cable: 120 cm

Benefits

- Easy positioning
- Shapeable shaft
- No friction (occluder device)
- Safe attachment/detachment

- Ⓐ : Loader
- Ⓑ : Y-Connector with tubing
- Ⓒ : Pre-shaped Sheath
- Ⓓ : Dilator
- Ⓔ : Pusher Cable
- Ⓕ : Removable torque device



- ① : Pre-shaped Sheath
- ② : Dilator
- ③ : Pusher Cable with torque device
- ④ : Y-Connector with tubing

Ordering Information / Technical Specification

Hyperion™ Orbit-A Delivery System

ONLY FOR USE WITH ADSO AND PFOO

Catalogue #		C-DS-A-8F	C-DS-A-9F	C-DS-A-10F	C-DS-A-12F	C-DS-A-14F
Loader	ID (F/mm/Inch)	8/2.77/0.109	9/3.08/0.121	10/3.38/0.133	12/4.0/0.157	14/4.67/0.184
	Length (cm)	11	11	11	14	14
Sheath	ID (F/mm/Inch)	8/2.77/0.109	9/3.08/0.121	10/3.38/0.133	12/4.0/0.157	14/4.67/0.0184
	Useable Length (cm)	80	80	80	80	80
	OD (mm)	3.37	3.74	4.04	4.80	5.53
	Angle°	135	135	135	135	135
Dilator	OD (F/mm)	8	9	10	12	14
	Useable Length (cm)	92	92	92	92	92
Pusher	Diameter (mm/inch)	1.8/0.071	1.8/0.071	1.9/0.075	2.1/0.083	2.1/0.083
	Length (cm)	120	120	120	120	120

① : Pre-shaped Sheath

② : Dilator

③ : Pusher Cable with torque device

④ : Y-Connector with tubing

